

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
L-3556

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name State FU
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	9. Well No. 4
4. Location of Well UNIT LETTER <u>B</u> <u>1</u> 1980 FEET FROM THE North LINE AND 1980 FEET FROM East THE LINE, SECTION 25 TOWNSHIP 18-S RANGE 34-E N.M.P.M.	10. Field and Pool, or Wildcat Airstrip Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 3965.3 GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled to a TD of 4005' and ran 9-5/8" casing set at 4005'. Cemented with 1355 SX Howco Lite cement with 8% salt/SX and 200 SX Class C cement with 2% CACL. Plugged down 9:00 p.m. 4-9-80. Circulated 125 SX. WOC 18 hours. Tested casing with 1500# for 30 min. Test OK. Reduced hole to 8-3/4" and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Bob Laws TITLE Admin. Analyst DATE 4-23-80

Orig. Signed By  
Jerry Sexton  
Dist. L. Supv.

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

0+4-NMOCD, H 1-Hou 1-Susp 1-BD 1-Mesa 1-Bass