

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

3a. Indicate Type of Lease
State ☒ Fee ☐

3. State Oil & Gas Lease No.

SUNDARY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

4. Name of Operator
AMOCO PRODUCTION COMPANY

5. Address of Operator
P. O. Box 68, Hobbs, NM 88240

6. Location of Well

UNIT LETTER I 1780 FEET FROM THE South LINE AND 480 FEET FROM
THE East LINE, SECTION 26 TOWNSHIP 18 RANGE 34 N.M.P.M.

7. Unit Agreement Name

8. Farm or Lease Name

State HQ

9. Well No.

2

10. Field and Pool, or Wildcat

Bone Springs

11. Elevation (Show whether DF, RT, GR, etc.)

3989 KB

12. County

Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☒

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOBS ☐

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to PXA the subject well.
MI X RUSU. Install BOP. POH with production equipment. RIH x set CIBP at 9100 ft. Cap with 35 ft class H neat cement. Spot 360 bbl of 10# brine with 25# gel/bbl from 9065 ft to surface. Spot 45 sx of class H neat from 7940-7725. (Top of Bone Springs at 7832'). Spot 63 sx of class H neat from 4100-3800. (Note: 9-5/8" casing shoe at 3970 ft and top of cement for 7" at 3925 ft). Perf at 400 ft with 4 JSPF with 3-1/8" or 4" gun. Pump down casing and put 7" x 9-5/8" annulus. Cement with 150 sx of class H neat cement. Cut off wellhead and install PXA marker. RD and MOSU.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by S. Brownlee S. Brownlee

TITLE Administrative Analyst

DATE 1-13-87

ORIGINAL SIGNED BY JERRY SEXTON

DISTRICT SUPERVISOR

APPROVED BY

TITLE

DATE

ADDITIONS OF APPROVAL, IF ANY:

RECEIVED
JAN 14 1987
ECO
HUMANITARIAN