

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR
THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR
P. O. BOX 4500 THE WOODLANDS, TEXAS

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FSL & 660' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☒
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) _____

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

RECEIVED
DEC 24 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

J. B. ...
EL PASO, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

The perforation work sited on form dated 11/5/80 has been done.
We now plan to proceed with the acidizing.

1. If acid job not successful, plug back perforations at 13,380 - 13,411' to 13,344'.
2. Reperforate 13,155 - 13,250'.
3. Acidize with 3,000 gallons Morrow - Flo acid with 1,000 SCF of Nitrogen per barrel.
4. Test and evaluate.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED L.H. Bohot L.H. Bohot TITLE Engr Supervisor DATE 12/18/80

(This space for Federal or State office use)

APPROVED BY (Orig. Sgd.) PETER W. CHESTER ACTING DISTRICT ENGINEER DATE DEC 30 1980

CONDITIONS OF APPROVAL, IF ANY: