COPY TO O. C. C.

Form Approved. Budget Bureau No. 42-R1424

UNIT[STATES DEPARTMENT OF THE INTERIOR	5. LE/ NM-12568 -A			
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME			
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME			
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Bondurant Federal Com.			
1. oil gas well other	9. WELL NO. 12 12 12 12 12 12 12 12 12 12 12 12 12			
2. NAME OF OPERATOR The Superior Oil Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Wildcat			
P. O. Box 71, Conroe, Texas 77301 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OF			
below.) AT SURFACE: 1980' FSL and 660' FEL AT TOP PROD. INTERVAL:	Sec. 1, T19S R32E 12. COUNTY OR PARISH 13. STATE Lea New Mexico			
AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. API NO.			
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD			

3581**'** GL

SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Run and cement casing

E: Report results of multiple completion or zone change on Form 9-330.)

U. S. GEOLOGICAL SURVEY HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drill 11" hole to 5250'. Ran 8-5/8" 32# S-80; K-55 to 5250' with DV tool at 1634'. The first cement stage was cemented with 800 sxs of class "C" + 6% D-20 (POZ 3) + 5#/sx Kolite + 8.5# salt + $\frac{1}{4}$ /sx of celloflake. Followed by 200 sxs class "H" w/2% CaCl₂. Open DV tool w/1200#. Circ. out no cement, had full returns. Cement second stage w/525 sxs class "C" 35/65 POZ + 6% POZ + 5#/sx Kolite + 5#/sx salt + 2% CaCl₂. Followed by 100 sx of class "C" w/2% CaCl2. Circulate out 55 sxs cement bumped plug @ 5:00 pm on 3-11-80.

Subsurface Safety Valve: Manu. and T	ype		Set @	<u>·</u> F	t.
18. I hereby certify that the foregoing SIGNED G. Bannantine	is true and correct	oup Mgr DATE _	5-6-80		_
	(This space for Federal or	State office use)	•		
APPROVED BY	TITLE	DATE _			

*See Instructions on Reverse Side

USGS (5), PRB, CRC, RAC, LH, RG, CF

ACCEPTED FOR RECORD

ROSWELL, NEW MEXICO