

AUXILIARY EQUIPMENT

DRAWWORKS

Emsco C-2 type III, 2000 HP
Grooved for 1-3/8" drill line
Parmac model 481 Hydromatic Brake

DERRICK

Ideco Fullview mast
143 ft. high
750,000 lb. static hook load

SUBSTRUCTURE

Ideco
24 ft. high
800,000 lb. casing capacity simultaneous with 400,000 lb. setback capacity

POWER SOURCE

3 - Caterpillar D-398 TA (diesel)
Horsepower - 2331

PUMPS

Emsco, model D-1000, 8" X 18", 1000 HP
National, 10P 130 triplex 1300 HP
High volume - low pressure mud mixing system

DRILL STRING

12,000 - 4-1/2" O.D., 16.6#/ft, Gr. E, 4-1/2" XH by 6" O.D. tool joints
Other grades of pipe available
Standard size collars available through 8"

PREVENTERS

1 - Hydril, model GK, 10" 5000 psi
1 - Cameron, model U-single, 1-Cameron, Model U-double, 11", 10,000 psi
1 - Payne Accumulator, 80 gallon capacity with 5 stations

OTHER EQUIPMENT

Crown block - Ideco, model 1024-2,500 ton capacity
Traveling block - Nationa, 450 ton capacity
Hood - Nationa, 450 ton capacity
Lightplants - 2, Capterpillar, 420 KW, 230/460 volts, A.C.
Swivel - Bethlehem, B-24
Mud tanks - three, 7' X 6' X 48'
Lights - Snelson, vapor proof
Desander - Thompson, 3 cone
Rotary table - Ideco, 27 1/2"
Bunk house - 10' X 60', wheeled trailer
Shale shaker - Link Belt, model NRM-145
Radio - General Electric, 100 watt
Crown-O-Matic