

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-26759 ✓
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. B-2148
7. Lease Name or Unit Agreement Name Leamex
8. Well No. 26
9. Pool name or Wildcat Leamex (Paddock)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL ☒ GAS WELL ☐ OTHER ☐	
2. Name of Operator Phillips Petroleum Company	
3. Address of Operator 4001 Penbrook Street, Odessa, TX 79762	
4. Well Location Unit Letter M : 660 Feet From The South Line and 990 Feet From The West Line Section 22 Township 17-S Range 33-E NMPM Lea County	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 4154' GL; 4165' RKB	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK ☐	REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐	ALTERING CASING ☐
PULL OR ALTER CASING ☐	COMMENCE DRILLING OPNS. ☐
OTHER: ☐	PLUG AND ABANDONMENT ☐
	CASING TEST AND CEMENT JOB ☐
	OTHER: Converted to an Oil Producer ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

05-27-93 - MIRU DDU. Press. test to 3500#. Held O.K. RIH with plug and set in 1.78" 'F' profile in on-off tool. Load tbg. and annulus with 10-lb brine. ND tree and WKM Type "U" x 7-1/16" 3M tubing head. Nu Class 3 BOP. GIH and retrieve tubing plug. Release packer. Circ. hole with 10-lb. brine. Start out of hole with tubing.

05-28-93 - Continue out of hole with tbg. and 4-1/2" Baker TSN-2 pkr. Lay down tubing. Check PBTD @6176'. PBTD @6166'. 10' Fill. PU 2-3/8" 4.7#, J-55 prod. tbg. and anchor. Anchor set @5700' and tbg. @6000'.

05-29-93 - GIH w/2"x1.25"x24' insert pump, 3925' of 3/4" Grade 'D' rods and 2125' of 7/8" Grade 'D' rods. Hang well on.

05-30-93 - Pump 24 hrs. Recvd. 12 BO; 75 BW; 40 Mcf gas.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE L. M. Sanders TITLE Supv. Regulatory Affairs DATE 06-02-93

TYPE OR PRINT NAME L. M. Sanders (915) TELEPHONE NO. 368-1488

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE JUN - 9 1993

CONDITIONS OF APPROVAL, IF ANY: