STATE OF NEW MEXICO NEHGY AND MINERALS DEPARTMENT

we, or contractives	T	
DISTRIBUTION		
SANTA FE		
FILE		
U.S.O.S.		
LAND OFFICE		
0.5	7	

OIL CONSERVATION DIVISION

DISTRIBUTION			Form C-103
SANTA FE	SANTA FE, NEW	/ MEXICO 87501 Revised 10-1-13	
FILE	•		5a. Indicate Type of Leuse
U.S.O.S.	1 .		State X Fee
OPERATOR	1		5. State Oil & Gas Lease No.
<u> </u>	API No. 30-025-26759		B-2148
SUNDR	RY NOTICES AND REPORTS ON	WELLS	
	OPOSALS TO DRILL OR TO DEFPEN OR PLUG B		
			7. Unit Agreement Name
werr X werr	OTHER-		
. Name of Operator			B. Farm or Lease Name
Phillips Petroleum	Company		Leamex
Address of Operator		9. Well No.	
Room 401, 4001 Penbrook, Odessa, TX 79762		26	
Location of Well			10. Field and Pool, or Wildcat
UNIT LETTER M	UNIT LETTER M 660 FEET FROM THE SOUTH LINE AND 990 FEET FRO		Leamex Paddock
	00 17 (
THE WEST LINE, SECTION	on22 TOWNSHIP17-S	33-E NANGE NMPM.	
mmmmm.		Dr. Dr. Gr.	
	15. Elevation (Show whether		12. County
	4154.3GR, 4164 F		Lea
	Appropriate Box To Indicate N	lature of Notice, Report or Otl	her Data
NOTICE OF IN	NTENTION TO:	SUBSEQUENT	T REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
CMPORARILY ABANDON		COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
ALL OR ALTER CASING	CHANGE PLANS	CASING TEST AND CEMENT JOB	to Dellardo de C
OTHER		other <u>Perf and treat</u>	In Paddock zone
	perations (Clearly state all pertinent deta	ils, and give pertinent dates, including	estimated date of starting any proposed
worky see Note 1103.			
8-19-82: MI & RU Gandy's PU. Pld rds & pmp. Instld BOP. Ran 20 jts.			
2-3/8" tbg w/Baker BP.			
-20,21,22-82: 20th, Ran 2-3/8" tbg. set Baker BP @ 6051. Loaded hole w/2% KC1			d hole w/2% KC1
wtr. Sptd 8 bbls 10% acetic acid. 22nd, Welex perfd 4-1/2" csg			
from 6031' - 6042' w/2 JSPF,11' - 22 holes. Ran 2-3/8" tbg w/Baker			2-3/8" tbg w/Baker
	"R" pkr. pkr set @ 5992'	, tbg set OE @ 6000'.	
	. 0.		
	15% NeFe HC1 w/one ball s	sealer/bbl in last 1000 g	gals acid.
0 1/ 01.	C-1 4 / hm 20 DO 10 DO	T T 1 41 - 1 - 4 - 1 - 1	DD 060511
8-24-82: Swbd 4 hrs, 29 BO, 18 BSW. Lowered tbg, latched on to BP @60. Rel BP. Pld tbg, pkr & BP. Ran 2-3/8" tbg, set OE @6095'.			or ecoet
	Rei Br. Fid tog, pki a i	br. Kall 2-3/6 tog, set t	JE 60032.
8-25-82:	Ran 2" X 1-1/4" X 16' pmp	n & set 06090' Pmp 17 h	re 70 BO 22 BSW
25 02. - 12 - 12 - 12 - 12 - 12 - 12 - 12 - 12	Kan Z X I I/4 X IO pmp	p u set 60000 . 1mp 17 m.	13, 79 BO, 22 BSW.
8-26/27/28/29-82:	Pmpg. Pmpd 96 hrs 419 BC	0. 297 BSW.	
		, 22. 25	
BOP Equip: Series 900,30	000# WP, double, w/one pi	pe rams, one set blind ra	ams, manually operated.
.f. I hereby certify that the information	above is true and complete to the best o	f my knowledge and belief.	
10/1/ 10.00	, et f		
SICHED THE	W.J. Mueller TITLE Sr.	Engrg. Specialist	September 1, 1982
CHIGINAL ORIGINAL	SIGNED BY		
JEPRV	SEXTON		SEP 7 1982
PPROVED BY UNSTRICT	I SUFR		DATE ULI (130L
ONDITIONS OF APPROVAL, IF ANY	- JUFK		. 2.

PTTTVED

SEP 3 1982

Pmpd 24 hrs. 137 BO, 31 BSW, GOR: 978, grind out 0.4% Pmp from String 39.7, 64--13" SPM w/2" X 1-½" X 16' pmp from GOR: 978, grind out 0.4% Pm

:28-08-8