

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

3-NMOC-D-HOBBS
1-R. J. STARRAK-TULSA
1-A. B. CARY-MIDLAND
1-PWS, ENGR.

1-BH, FIELD CLK
1-EF, FOREMAN
1-FILE

Form C-103
Supersedes Old
C-102 and C-101
Effective 1-1-65

50. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
E-7653
7. Unit Agreement Name
8. Form of Lease Name
State "AP"
9. Well No.
1
10. Field and Pool, or Valued
Vacuum Abo Reef
12. County
Lea

SUNDARY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR NOTICES TO ABANDON OR TO REOPEN OR RELOCATE TO A DIFFERENT RESERVOIR. USE APPLICATION FOR REPAIR OF (FORM C-101) FOR SUCH PURPOSES.)

1. Name of Operator	2. Name of Operator
Getty Oil Company	Getty Oil Company
3. Address of Operator	3. Address of Operator
P. O. Box 730, Hobbs, NM 88240	P. O. Box 730, Hobbs, NM 88240
4. Location of Well	4. Location of Well
UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 18-S RANGE 35-E N.M.P.M.	UNIT LETTER L 1980 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 9 TOWNSHIP 18-S RANGE 35-E N.M.P.M.

15. Elevation (Show whether DF, RT, CR, etc.)
3940.5 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
PULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6/24/80 Rial Drilling Co. spudded 15" hole at 3:00 p.m. Drilled to 195' in rock and sand. SD. Waited on csg.

6/25/80 Drilled 15" hole to 300'. Ran and set 8 jts. 11 3/4" (281') 42#, H-40, ST&C csg. set at 300'. Guide shoe set at 299'.

Western Co. cemented csg. with 215 sxs Class "C" cement, 2% CaCl, 1/4# cello flakes, and 5# gilsonite. Circulated 85 sxs. In 3 hrs. the cement was at 15'. Mixed 35 sxs Ready Mix - cement at top. Plug down at 2:15 p.m. WOC 18 hrs. Tested to 1200# for 30 min. OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED: R. Crockett TITLE: Area Superintendent DATE: 6-27-80

Orig. Signed by
John Runyan
Geologist

APPROVED BY: _____ TITLE: _____ DATE: _____

CONDITIONS OF APPROVAL, IF ANY:

JUN 30 1980