## New Mexico Oil Conservation Division, District I

Form 3160-5 (August 1999) TED STATES

1625 N. French!

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

BUREAU OF LAND MANAGEMENT

DEPARTMENT OF THE INTERIOR Hobbs, NM 88240

5. Lease Serial No.

SUNDRY NOTICES AND	REPORTS	ON	WELLS	
--------------------	---------	----	-------	--

Do not use this form for proposals to drill or to re-enter an

NM01177A 6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on reverse side			7. If Unit or CA/Agreement, Name and/or		
1. Type of Well  X Oil Well Gas Well Other  2. Name of Operator				8. Well Name Federal AB	
Occidental Permian Limited Partnership  3a. Address  3b. Phone No. (include area code)			9. API Well No. 30-025-26829		
P.O. Box 50250, Midland, TX 79710-	50250, Midland, TX 79710-0250 915-685-5717			10. Field and	Pool, or Exploratory Area
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 660 FSL 2130 FEL SWSE (O) Sec 33 T18S REFE		Corbin Wolfcamp, South  11. County or Parish, State			
				Lea	NM
12. CHECK APPROPRIATE	BOX(ES) TO INI	DICATE NATURE OF I	NOTICE, REF	PORT, OR OTH	HER DATA
TYPE OF SUBMISSION	TYPE OF ACTION				
X Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production Reclamate	on (Start/Resume)	Water Shut-Off Well Integrity
Subsequent Report	Casing Repair	New Construction	Recompl		Other
Final Abandonment Notice	Change Plans  Convert to Injecti	X Plug and Abandon on Plug Back	Temporar Water Di	rily Abandon sposal	

following completion of the involved operations. If the operation results in a multiple completion of testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the final site is ready for final inspection.)

PERFS-11203-11294' (PA) 4449-4467' (BO) PBTD-4005' TD-13665'

CTBP-11150'w/35'cmt, 5100' w/ 35'cmt, 4005' no cmt

13-3/8" 48# Csg @ 438' W/ 500sx, 17-1/2" Hole, TOC-Circ

9-5/8" 40# Csg @ 5000' W/ 2800sx, 12-1/4" Hole, TOC-1120'-TS

5-1/2" 17-20-23# Cag @ 11428' W/ 2100ax, 8-3/4" Hole, TOC-1885'-TS

1. RIH & Drill out CIBP's @ 4005' & 5100'.

- ax @ 9350-9<del>=50 9</del>200 °
- x @ 7500-7-200
- 4. M&P HEX @ 5050-4550 4900'
- 5. \*RIH & set CIBP @ 4400', Dump 5sx cmt to 4365' or \*M&P 25sx @ 4400-4300', WOC-TAG
- 6. M&P 25sx @ 3010-2910'
- 7. PERF 5-1/2" & 9-5/8" @ 488', sqz w/ 80sx TO 388', WOC-TAG
- 8. M&P 10sx cmt surface plug

10# MLF between plugs

## SEE ATTACHED FOR CONDITIONS OF APPROVAL

14. I hereby certify that the foregoing is true and correct Name (Printed/Typed)  David Stewart	Title Sr. Regulat	ory Analyst			
On Still	Date E(C	102			
APPROVED THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by (ORIG. SGD.) DAVID R. GLASS	Title	Date			
Conditions of approval, 1160, 20 and 1160 Approval of this notice does no certify that the applicant hords legal or equitable title to those rights in the which would entitle the applicant to conduct operations thereon.					
Title 18 U.S.C. Section 1001, and Title 43 U.S.C. Section 1212, makes it a c States any false, figurious of traudilent statements or representations as to an	rime for any person knowingly and willf ny matter within its jurisdiction.	ully to make to any department or agency of the United			

## OCCIDENTAL PERMIAN LTD. FEDERAL AB #1 (CURRENT) SEC 33 T18S R37E LEA NM

TD: 13665'

4005.0 - 4005.0' CIBP 2/94

5065.0 - 5100.0' CEMENT PLUG 3sx 5100.0 - 5100.0' CIBP 12/92 0.0 - 438.0' 17-1/2" OD HOLE 0.0 - 438.0' CEMENT 500sx-CIRC 0.0 - 438.0' 13-3/8" OD SURF CSG

438.0 - 5000.0' 12-1/4" OD HOLE 1120.0 - 5000.0' CEMENT 2800sx-TS 0.0 - 5000.0' 9-5/8" OD INT CSG

4449.0 - 4467.0' ABANDONED PERFS QUEEN

5000.0 - 13665.0' 8-3/4" OD HOLE 1885.0 - 11428.0' CEMENT 2100sx-TS 0.0 - 11428.0' 5-1/2" OD PROD CSG

11203.0 - 11234.0' ABANDONED PERFS WOLFCAMP 11360.0 - 11700.0' CEMENT PLUG 180sx-8/80 11983.0 - 12175.0' CEMENT PLUG 85sx-8/80

## OCCIDENTAL PERMIAN LTD. FEDERAL AB #1 (PROPOSED) SEC 33 T18S R37E LEA NM

0.0 - 438.0' 17-1/2" OD HOLE 0.0 - 75.0' CEMENT PLUG 10sx 0.0 - 438.0' CEMENT 500sx-CIRC 0.0 - 438.0' 13-3/8" OD SURF CSG 388.0 - 488.0' CEMENT PLUG 80sx 488.0 - 488.0' SQUEEZE PERFS 438.0 - 5000.0' 12-1/4" OD HOLE 2910.0 - 3010.0' CEMENT PLUG 25sx 1120.0 - 5000.0' CEMENT 2800sx-TS 0.0 - 5000.0' 9-5/8" OD INT CSG 4365.0 - 4400.0' CEMENT PLUG 5sx 4449.0 - 4467.0' ABANDONED PERFS QUEEN 4400.0 - 4400.0' CIBP 4950.0 - 5050.0' CEMENT PLUG 25sx 7400.0 - 7500.0' CEMENT PLUG 25sx 5000.0 - 13665.0' 8-3/4" OD HOLE 1885.0 - 11428.0' CEMENT 2100sx-TS 0.0 - 11428.0' 5-1/2" OD PROD CSG 9250.0 - 9350.0' CEMENT PLUG 25sx 11203.0 - 11234.0' ABANDONED PERFS WOLFCAMP 11115.0 - 11150.0' CEMENT PLUG 11/91 11360.0 - 11700.0' CEMENT PLUG 180sx-8/80 11983.0 - 12175.0' CEMENT PLUG 85sx-8/80

TD: 13665'