

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN THE INDICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 17435-4

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Shelly Federal Comm.

9. WELL NO.

#1

10. FIELD AND POOL, OR WILDCAT
Undesignated First Bone
Spring Sand11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec. 5, T19S, R32E

12. COUNTY OR PARISH 13. STATE

Lea N.M.

SUNDRY NOTICES AND REPORTS **RECEIVED**
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

MAR 6 1981

1. OIL WELL ☐ GAS WELL ☒ OTHER2. NAME OF OPERATOR
PETROLEUM DEVELOPMENT CORPORATION U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO3. ADDRESS OF OPERATOR
9720 B Candelaria NE, Albuquerque, NM 871124. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FNL, 660' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3,669 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON* ☐REPAIR WELL ☐CHANGE PLANS ☐

(Other) Recompletion

XX

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☒REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT* ☐(Other) ☐(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Approx. 3/5/81:

1. Set cast iron bridge plug at 12,500'. Dump 30' of cement on plug.
2. Perforate at 8,480'. Cement with 250 sacks of Class "H" cement; bring cement to top at 7,500'.
3. ~~Drill out cement retainer and cement.~~
4. Perforate from 8,528' - 8,560' with 2 JHPF. Acidize with 1,000 gal. of 15% MSR acid. Swab. Bone Spring
5. Fracture treat, if necessary. Place on production.

RECEIVED

MAR 11 1981

U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

J.E. Johnson

TITLE

President

DATE 3/2/81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

APPROVED

MAR 10 1981

JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side