

**UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY**

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Coquina Oil Corporation

3. ADDRESS OF OPERATOR
P. O. Drawer 2960 Midland, TX 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FNL & 660' FEL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other) Cmt 8-5/8" casing			X

5. LEASE
NM 17435-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
--

7. UNIT AGREEMENT NAME
--

8. FARM OR LEASE NAME
Shelly Com Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Undesignated

11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 5, 19S, 32E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3669' GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drilled 12 1/4" hole to 4195'. Ran 8-5/8" casing as follows: 41 jts, 1729' of 28#, K-55, STC; 58 jts, 2316' of 24#, K-55, STC; and 4 jts, 163' of 28#, K-55 STC 8-5/8" casing. Casing set at 4196'. Cmt'd w/325 sx Howco Lite. Tail w/300sx C1 C, 1/4# flocele/sx. Bumped plug w/700#. Checked float OK. Plug down at 4:25 PM, 8/8/80. Opened DV Tool at 1247'. Circulated 4 hours. Cmt'd 2nd stage w/550 sx Howco Lite. Displaced w/78 bbls. Cmt did not circ. WOC 5 hours. Run 1" tagged TOC at 220'. Cmt'd w/120 sx Howco Lite. Circ 20 sx to pit. WOC 18 hours.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED G. L. Crain TITLE Drilling Manager DATE 8/13/80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____
CONDITIONS OF APPROVAL, IF ANY: _____U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

ACCEPTED FOR RECORD

AUG 21 1980

U. S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO