

	O. D.	I. D.	LENGTH	DEPTH
Drill Pipe or Tubing				
Drill Collars				
Reversing Sub	6.00"	3.00"	1.00'	
Water Cushion Valve				
Drill Pipe	4.50"	3.826"	9119'	
Drill Collars	6.00"	2.25"	486'	
Handling Sub & Choke Assembly				
Dual CIP Valve				
Dual CIP Sampler X OVER	6.00"	2.25"	1.00'	
Hydro-Spring Tester	5.00"	.75"	4.00'	9610'
Multiple CIP Sampler	5.00"	.75"	5.00'	
Extension Joint	5.00"	.87"	10'	
AP Running Case	5.00"	3.25"	4.00'	9629'
Hydraulic Jar	5.00"	1.75"	5.00'	
VR Safety Joint	5.00"	1.00"	3.00'	
Pressure Equalizing Crossover				
Packer Assembly	7.00"	1.68"	5.00'	9641'
Distributor	5.00"	1.53"	2.00'	
Packer Assembly	7.00"	1.68"	5.00'	9648'
Flush Joint Anchor				
Pressure Equalizing Tube				
Blanked-Off B.T. Running Case				
Drill Collars				
Anchor Pipe Safety Joint				
Packer Assembly				
Distributor				
Packer Assembly				
Anchor Pipe Safety Joint				
Side Wall Anchor X OVER	5.75"	2.25"	1.00'	
Drill Collars X OVER	6.00"	2.25"	32'	
Flush Joint Anchor	5.75"	3.50"	12'	
Blanked-Off B.T. Running Case	5.75"	3.50"	5.00'	9697'
Total Depth				9701'