

|                               | O. D. | I. D.  | LENGTH | DEPTH |
|-------------------------------|-------|--------|--------|-------|
| Drill Pipe or Tubing          |       |        |        |       |
| Drill Collars                 |       |        |        |       |
| Reversing Sub                 | 5.50" | 2.50"  | 1.00'  |       |
| Water Cushion Valve           |       |        |        |       |
| Drill Pipe                    | 4.50" | 3.826" |        |       |
| Drill Collars                 | 6.25" | 2.50"  | 462'   |       |
| Handling Sub & Choke Assembly |       |        |        |       |
| Dual CIP Valve                |       |        |        |       |
| Dual CIP Sampler              |       |        |        |       |
| Hydro-Spring Tester           | 5.00" | .75"   | 5.31'  |       |
| Multiple CIP Sampler          | 5.00" | 2.38"  | 4.52'  |       |
| Extension Joint               | 5.00" | .87"   | 9.16'  |       |
| AP Running Case               | 4.75" | 2.50"  | 4.00'  |       |
| Hydraulic Jar                 | 5.00" | .75"   | 5.00'  |       |
| VR Safety Joint               | 5.00" | 1.00"  | 2.80'  |       |
| Pressure Equalizing Crossover |       |        |        |       |
| Packer Assembly               |       |        |        |       |
| Distributor                   |       |        |        |       |
| Packer Assembly               |       |        |        |       |
| Flush Joint Anchor            |       |        |        |       |
| Pressure Equalizing Tube      |       |        |        |       |
| Blanked-Off B.T. Running Case |       |        |        |       |
| Drill Collars                 |       |        |        |       |
| Anchor Pipe Safety Joint      |       |        |        |       |
| Packer Assembly               | 7.00" | 1.53"  | 4.00'  |       |
| Distributor                   | 5.00" | 1.68"  | 2.00'  |       |
| Packer Assembly               | 7.00" | 1.53"  | 4.00'  |       |
| Anchor Pipe Safety Joint      | 5.75" | 2.50"  | 4.00'  |       |
| FLUSH JOINT ANCHOR            | 5.75" | 2.50"  | 15'    |       |
| Drill Collars                 | 6.25" | 2.50"  | 153'   |       |
| Flush Joint Anchor            | 5.75" | 2.50"  | 20'    |       |
| Blanked-Off B.T. Running Case | 5.75" | 2.50"  | 6.00'  |       |
| Total Depth                   |       |        |        | 9950' |