

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

API No. 30-025-26928

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
B-2131	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL <input checked="" type="checkbox"/> GAS <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name East Vacuum Gb/SA Unit
2. Name of Operator Phillips Petroleum Company		8. Farm or Lease Name East Vacuum Gb/SA Unit, Tr 0449
3. Address of Operator Room 401, 4001 Penbrook St., Odessa, Texas 79762		9. Well No. 002
4. Location of Well UNIT LETTER D 980 FEET FROM THE North LINE AND 90 FEET FROM THE West LINE, SECTION 4 TOWNSHIP 18-S RANGE 35-E NMPM.		10. Field and Pool, or Wildcat Vacuum Gb/SA
15. Elevation (Show whether DF, RT, GR, etc.) 3949.5 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	
		OTHER Total Depth <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-13-80 MI Cactus Drlg. Spud w/12-1/4" bit to 353'. Ran 8-5/8" 24#, K-55 csg set at 353'. Cmdt w/400 sxs C1 "H" w/2% CaCl₂, 1/4# sx Flocele. Circ 90 sxs to surface. Tstd csg 10 hrs after plug down. Temp of cmt 65°, formation temp in zone 65°, cmt strength at time of csg test 1000 psi, time cmt in place prior to test, 12 hrs, tstd csg and BOP 1000#, o.k. Drld ahead w/7-7/8" bit.

10-22-80 Drld to 4802', TD. Logged.

10-23-80/24 Completed logging.

10-25-80 Ran 5-1/2" 14#, K-55 csg set at 4782'. Cmdt w/1160 sxs TLW, 12#/sx salt, followed w/305 sxs C1 "H" w/5#/sx salt. Circd 75 sxs surface.

10-26-80 Released rig; prep to complete.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Sr. Engineering Specialist DATE Novmeber 4, 1980

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: