

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
E-1632-1	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator		8. Farm or Lease Name
Anadarko Production Company		New Mex. "U" State
3. Address of Operator		9. Well No.
P.O. Box 806 Eunice, New Mexico 88231		5
4. Location of Well		10. Field and Pool, or Wildcat
UNIT LETTER <u>F</u> , <u>2080</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM		E.K. Queen East
THE <u>West</u> LINE, SECTION <u>28</u> TOWNSHIP <u>18S</u> RANGE <u>34E</u> N.M.P.M.		
15. Elevation (Show whether DF, RT, GR, etc.)		12. County
4029 GR		Lea

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. 2-12-81- Drilled 7-7/8" hole from 432' to 4999' TD KB.
2. Ran 116 jts (4999') of 4 1/2" 10.5# K-55 ST&C Range 3. (New) w/float collar & guide shoe.
3. Cemented w/1375 sx Halliburton Light Cement w/1/4# Flocele & 15# salt. Followed w/400 sx Class H cement w/3/4 of 1 1/2 CFR-2, 10# sand & 5# salt. Plug Down 6:00 P.M. 2-21-81.
4. Circulated 145 sx of cement to pit.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Edward D. Heckelt TITLE Production-Foreman DATE 2-27-81

APPROVED BY Jerry Saxton TITLE Dist. L. Supv. DATE Mar 1 1981

CONDITIONS OF APPROVAL, IF ANY: