

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ well ☐ other ☐
2. NAME OF OPERATOR  
Amoco Production Company
3. ADDRESS OF OPERATOR  
P. O. Box 68 Hobbs, NM 88240
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1980' FNL & 660' FWL, Sec. 26  
AT TOP PROD. INTERVAL: (Unit E, SW/4, NW/4)  
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

## REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
- FRACTURE TREAT ☐
- SHOOT OR ACIDIZE ☐
- REPAIR WELL ☐
- PULL OR ALTER CASING ☐
- MULTIPLE COMPLETE ☐
- CHANGE ZONES ☐
- ABANDON\* ☐
- (other) ☐

## SUBSEQUENT REPORT OF:

- ☒
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐
- ☐

5. LEASE  
NM-12412
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME  
Federal AW
9. WELL NO.  
1
10. FIELD OR WILDCAT NAME  
Wildcat Morrow
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
26-19-23 32
12. COUNTY OR PARISH  
Lea
13. STATE  
NM
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3581.8' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to a TD 13520' and ran 1305' 5-1/2" 23# N-80 casing, 5330' 5-1/2" 20# N-80 casing, and 6885' 5-1/2" 17# N-80 casing set at 13520'. Cemented with 350 SX Halliburton Lite (with additives), 350 SX Class H cement (with additives), 1500 SX Halliburton Lite (with additives) and tailed in with 350 SX Class H cement (with additives). Plugged down at 4:00 p.m. 1-3-81. Ran temperature survey and found top of cement at approx. 3055'. Will test casing when completion unit moves in.

0+4-USGS, H 1-Hou 1-Susp 1-GLF 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Ronald L. Fisher*

TITLE

Admin. Analyst

DATE

1-14-81

APPROVED BY

ACCEPTED FOR RECORD

PETER W. CHESTER

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

JAN 20 1981

U.S. GEOLOGICAL SURVEY  
ROSWELL, NEW MEXICO

See Instructions on Reverse Side