

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☐ other2. NAME OF OPERATOR
Amoco Production Company3. ADDRESS OF OPERATOR
P. O. Box 68, Hobbs, NM 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 660' FWL, Sec. 26
AT TOP PROD. INTERVAL: (Unit E, SW/4, NW/4)
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☒
☐
☐
☐
☐
☐
☐
☐
☐RECEIVED
OCT 16 1980
U. S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

On 10-6-80, MGF Drilling Co. (rig #26) spudded a 17-1/2" hole at 2:00 p.m. Drilled to a TD of 512' and ran 48# H-40 13-3/8" casing set at 512'. Cemented with 475 SX Class C cement with 1% CaCl. Bumped plug at 11:30 a.m. 10-7-80. Circulated 120 SX. WOC 18 hr. Tested casing with 600# for 30 min. Test OK. Reduced hole to 12-1/4" and resumed drilling.

0+4-USGS, H 1-Hou 1-LBG 1-Susp 1-W. Stafford, Hou

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Benton Green TITLE Ast. Adm. Analyst DATE 10-13-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: