

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-27139

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

N. HOBBS (G/SA) UNIT  
SECTION 32

8. Well No.

132

9. Pool name or Wildcat

HOBBS (G/SA)

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☐

GAS  
WELL ☐

OTHER

INJECTOR

2. Name of Operator

SHELL WESTERN E&P INC.

3. Address of Operator

P. O. BOX 576, HOUSTON, TX 77001 (WCK 4435)

4. Well Location

Unit Letter L : 1400 Feet From The SOUTH Line and 1300 Feet From The WEST Line

Section

32

Township

18S

Range

38E

NMPM

LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3629' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

REMEDIAL WORK ☐

ALTERING CASING ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

PULL OR ALTER CASING ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Profile Modification--Run 3-1/2" lnr, Perf ☒

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1. Pres tst ann to 500# for 30 min.

2. POH w/inj equip.

3. CO to 4466' (PBTD).

4. Run ±606' 3-1/2" Fiberglass lnr w/metal imbedded colrs.

5. Hang TOL @ ±3820'.

6. Cmt lnr w/55 sx Cls "C" cmt + 4#/sk gilsonite + 1/4#/sk flocele.

7. CO to TOL. Pres tst lnr top to 500#.

8. CO lnr to top of landing colr (4460').

9. Run CBL from 4460' to abv TOL (3820').

10. Perf SA 4076' - 4240' (2 JSPF).

(CONT'D ON REVERSE SIDE)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

J. H. Smitherman

TITLE

REGULATORY SUPV.

DATE

1-22-90

TYPE OR PRINT NAME

J. H. SMITHERMAN

(713) 870-3797

TELEPHONE NO.

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

JAN 25 1990

CONDITIONS OF APPROVAL, IF ANY:

11. Acidz perf's 4076' - 4240' w/7000 gals 15% HCl.
12. Install inj equip, stringing seal assy into perm pkr/hgr @ 3820'.
13. Pres tst ann to 300# for 30 min & ret to inj.

RECEIVED

JAN 24 1990

CCD  
HOBBS