

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I

1625 N. French Drive, Hobbs, NM 88240

OIL CONSERVATION DIVISION

310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

WELL API NO.	30-025-27198
5. Indicate Type of Lease	FED <input type="checkbox"/> STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	NORTH HOBBS (G/SA) UNIT
Section	18
8. Well No.	242
9. Pool name or Wildcat	HOBBS (G/SA)

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101 FOR SUCH PROPOSALS.)	
1. Type of Well:	Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other Temporary Abandoned
2. Name of Operator	OCCIDENTAL PERMIAN, LTD.
3. Address of Operator	1017 W STANOLIND RD.
4. Well Location	Unit Letter <u>N</u> <u>1200</u> Feet From The <u>SOUTH</u> Line and <u>2600</u> Feet From The <u>WEST</u> Line Section <u>18</u> Township <u>18-S</u> <u>38-E</u> NMPM LEA County
10. Elevation (Show whether DF, RKB, RT GR, etc.)	3665' GL

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
PLUG AND ABANDON <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG & ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER: <input type="checkbox"/>	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Well is TA'd with CIBP @4100' capped w/35' cmt. TOC @4065'.
Circ Mud Gel from 4065' to 2650'.
Spot cmt from 2650' to 2550'. Bot of Anhy @2600'. --TAG
Circ Mud Gel from 2550' to 1950'.
Perf 5.5" csg @1950. TOC @1960'.
Set cmt ret @1900'. Circ cmt to surface.
Spot cmt from 1900' to 1800'. Top of Anhy @1850'.
Circ Mud Gel from 1800' to 1650'.
Spot cmt from 1650' to 1550'. Bot of 8-5/8" csg @1600'. -TAG
Circ Mud Gel from 1550' to 400'.
Spot cmt from 400' to 300'.
Circ Mud Gel from 300' to 60'.
Spot cmt from 60' to surface.
Cut off csg and installed dry hole marker 4' above ground level. NHU 18-241, UL "N", Sec. 18, TWN 18-S, RNG 38-E.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Robert Gilbert TITLE SR. ENG. TECH DATE 07/08/2002
TYPE OR PRINT NAME Robert Gilbert TELEPHONE 505/397-8206
NO.

(This space for State Use)

APPROVED BY OC FIELD REPRESENTATIVE DATE AUG 12 2002
CONDITIONS OF APPROVAL IF ANY: