

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P O BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-79

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE APPLICATION FOR PERMIT L-1 (FORM C-101) FOR SUCH PROPOSALS.

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Mesa Petroleum Co.	8. Farm or Lease Name Jan
3. Address of Operator P. O. Box 2009 / Amarillo, Texas 79189	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>34</u> TOWNSHIP <u>18S</u> RANGE <u>35E</u> N.M.P.M.	10. Field and Pool, or Wildcat Undes. Scharb Bone Springs
15. Elevation (Show whether DF, RT, GR, etc.) 3857.5' GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐
PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER WC perfs & plug back to Bone Springs ☒
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Drilled out 5½" casing to PBTD of 10,895' on 8-24-83. Ran GR-CBL-CCL --- TOC @ 8690'. Perf'd Lower WC from 10,786' -- 10,842'; .45" entry; total of 35 holes. Acidized on 8-27-83 with 12,000 gal 15% HCl + 138 BS. (Cement squeeze perfs @ 10,695, 2 JSPF -- appear to be open and communicating with WC perfs.) Perf'd upper WC from 10,078 -- 10,283'; .45" entry; total of 45 holes. Acidized on 9-3-84 with 8750 gals 15% HCl + 90 BS. Set CIBP @ 9500' plus 20' cement on 9-7-83. Perf'd Bone Springs from 8920' -- 9311' on 9-7-83. Acidized with 7000 gal NE-FE acid + 70 BS. Rigged up swab and began testing well on 9-8-83.

XC: NMOCD-H(0+2), CEN RCDS, ACCTG, MAT CONT, OPS(FILE), MIDLAND, ROSWELL

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R. E. Marks TITLE REGULATORY COORDINATOR DATE 9-29-83

ORIGINAL SIGNED BY EDDIE SEAY

OIL & GAS INSPECTOR

APPROVED BY _____ TITLE _____ DATE OCT 3 1983

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

SEP 30 1983

O.C.D.
HOBBS OFFICE