

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly drilled or deepened well. It shall be accompanied by a complete log of all electrical and radioactivity logs run in the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured vertically in the case of directionally drilled wells, true vertical depth shall also be reported. For multiple completions, from top through bottom shall be reported for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required, see Rule 1465.

INDICATE FORMATION LOGS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____ 1,702'	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
T. Salt _____	T. Anoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates _____ 3,178'	T. Miss _____ 10,934'	T. Cliff House _____	T. Leadville _____
T. 7 River _____	T. Devonian _____ Not Deep Enough	T. Merced _____	T. Madison _____
T. Queen _____ 4,400'	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres _____ 4,930'	T. Simpson _____	T. Gallup _____	T. Ignacio Quartz _____
T. Glorieta _____	T. Marlow _____	T. Rose Greenhorn _____	T. Granite _____
T. Paddock _____	T. Ellendörfer _____	T. Dakota _____	T. _____
T. Elnorby _____	T. Gr. Wash _____	T. Morrison _____	T. _____
T. Teller _____	T. Granite _____	T. Teddie _____	T. _____
T. Dardard _____	T. Delaware Sand _____	T. Enid _____	T. _____
T. Abilene _____	T. Fox Spring _____ 6,844'	T. Warsaw _____	T. _____
T. Wolfcamp _____ 8,812'	T. _____	T. Charlie _____	T. _____
T. Penn _____ 10,590'	T. _____	T. Permian _____	T. _____
T. Citrus (B&L C) _____	T. _____	T. Penn. "A" _____	T. _____

No. 1, from _____ 10,040' to _____ 10,052' OIL OR GAS SANDS OR ZONES

No. 2, from _____ to _____

No. 3, from _____ to _____

No. 4, from _____ to _____

No. 5, from _____ to _____

No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rise of water in hole and elevation to which water rose in hole.

No. 1, from _____ to _____ feet.

No. 2, from _____ to _____ feet.

No. 3, from _____ to _____ feet.

No. 4, from _____ to _____ feet.

XXXXXXXXXX OF RECORD (Attach additional sheet, if necessary)

From	To	Thickness in Feet	XXXXXXXXXX Lithology	From	To	Thickness in Feet	XXXXXXXXXX Lithology
-0-	1702	1702	Red shale, salt & anhyd.	10590	10800	210	Limestone
1702	2020	318	Anhydrite (bedded)	10800	10934	134	Shale
2020	3178	1158	Shale	10934	11665	731	Limestone
3178	3360	182	Sand		(TD)		
3360	5600	2240	Dolomite				
5600	6844	1244	Shale w/lime stringers				
6844	8812	1968	Dolomite w/sand stringers				
8812	9360	548	Shale w/sand				
9360	9540	180	Dolomite				
9540	10040	500	Shale w/sand				
10040	10300	260	Dolomite w/chert				
10300	10590	290	Shale w/dolomite & chert				

RECEIVED

MAR 1965

OFFICE