

UNITED STATES GEOLOGICAL SURVEY
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form approved.
Budget Bureau No. 42-11424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-24162

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Scott "E" Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lusk Morrow, North

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 28-T18S-R32E

12. COUNTY OR PARISH 13. STATE

Lea

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, CR, etc.)

3710' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Casing

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

TD 13,100' 7-13-81. Set 100 sack cement plugs 12,900'-13,100'; 12,150'-12,350'; 10,150'-10,350'. Set 200 sack cement plug 9225'-8720'. Drilled cement 8720'-9000', circulate hole. RU & ran 113 jts 5½" 17# N-80 LT&C (3507'), 128 jts 5½" 17# K-55 LT&C (5334'), 4 joints and 1 cut joint 5½" 17# N-80 LT&C (140') (8981') set at 9000', FC at 8965'. Cement with 225 sacks Class "G" with Halad 9. Plug down 10:50 P.M., 7-20-81. TSTOC 7900'. Test casing 2000#.

RECEIVED
AUG 7 1981

OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED ROGER A. CHAPMAN

TITLE Area Drilling Superintendent DATE 8-4-81

(This space for Federal or State office use)

APPROVED BY AUG 11 1981

CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE _____

U.S. GEOLOGICAL SURVEY