

Form 9-331
(May 1963)UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-24162

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Scott "E" Federal Com

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Lusk Morrow, North

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Sec 28-T18S-R32E

12. COUNTY OR PARISH 13. STATE

Lea

NM

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)1. OIL WELL ☐ GAS WELL ☒ OTHER

2. NAME OF OPERATOR

Gulf Oil Corporation

3. ADDRESS OF OPERATOR

P. O. Box 670, Hobbs, NM 88240

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3710' GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Casing

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 6:00 P.M., 6-11-81. RU & ran 97 joints and 1 cut joint 8-5/8" 28# S-80 ST&C (4137') set at 4158', FC at 4111'. Cement with 1500 sacks Gulfmix, 200 sacks Class "C" neat. Plug down 1:00 P.M., 6-12-81. Circulate cement to surface. WOC 18 hours. Test casing 1500#. Drill cement, float, shoe. Drilling 7-7/8" hole 8:30 P.M., 6-13-81.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Area Drilling Superintendent DATE 6-18-81

(This space for Federal or State office use)

APPROVED BY
CONDITIONS OFACCEPTED FOR RECORD
ROGER A. CHAPMAN

TITLE

DATE

JUN 24 1981