ABANDON\*

## UNITED STATES P 5 37 1960 DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

<b>J</b> .	LEASE		
	MM	14000	)

6.	IF INDIAN,	ALLOTTEE	OR TRIBE NAM

6.	IF INDIAN, ALLOTTEE OR TRIBE NAMI	E
	N/A	

7.	UNIT	<b>AGREEMENT</b>	
		N,	/A

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME N/A  8. FARM OR LEASE NAME
1. oil gas other	New Mexico Federal "35" fell 9. WELL NO.
2. NAME OF OPERATOR	2
William E. Hendon, Jr.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Querecho (Queen)
601 N. Loraine, Suite 111	11. SEC., T., R., M., OR BLK. AND SURVEY OR
<ol><li>LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)</li></ol>	Sec. 35, T-/8-S, R-32-E
AT SURFACE: 760 FNL & 1880 FEL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE Lea New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	1982 利用

U.S. GEOLOGICAL SURVEY 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Moved in pulling unit. Found 50 psig on tbg. Pulled tbg. out of hole. Perforated 1 JSPF: 2952, 2954, 2956, 2960, 2961, 2967, 2969, 2971, 2972, 2973, 3026,3028, 3030, 3032. Treated with 2000 gal. 15% NE HCl. Perfs broke at 2500 psig and 1-1/2 BPM. Treated at 1900 psig. ISIP-1650 psig. Opened up after 1/2 hour, well flowed back less than 1 bbl. and died. RU to swab and swabbed tbg. dry in 4 runs. Recovered about 15 bbls. FL at SN. No color, cut, oil, gas. No shows. RIH tbg. and SN and flanged up wellhead. Moved off well. Lease SI for evaluation.

OIL & GAS

Subsurface Safety Valve: Manu. and Type	N/A	Set @ Ft.	
18. I hereby certify that the foregoing is true and co	prrect		
SIGNED INTER CAR BEFORD	e Opr. Mgr.	ATE January 27, 1982	
(Orig. Sgl.) PETER W. CHLOLLE	ce for Federal or State office use)	**************************************	
APPROVED BY		DATE	

MINERALS MANAGEMENT SERVICE ROSWELL, NEW MEXICO

(other) perforating and testing

**BECEJARO** UNITER A EXIMPLA

O.C.P. HOBBS