

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☐ well other ☒ dry hole
2. NAME OF OPERATOR
William E. Hendon, Jr.
3. ADDRESS OF OPERATOR
601 N. Loraine, Suite 111
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 760 FNL & 1880 FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

SUBSEQUENT REPORT OF:

- ☐
☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM 014000
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
N/A
7. UNIT AGREEMENT NAME
N/A
8. FARM OR LEASE NAME
New Mexico Federal "35" Fed.
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Querecho (Queen)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 35, T-18-S, R-32-E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
N/A
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3729 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

This well has been declared to be a dry hole by the operator due to absence of hydrocarbons in any prospective productive horizon contained within the wellbore. Telephone conversation with George Stewart, USGS, Roswell, yielded verbal approval for following plugging method: (1) set CIBP at 3175' between two sets of perfs and cap with 35 linear feet of cement; (2) CIBP at 2900' on top of top perfs capped with 35 linear feet of cement; (3) 100 feet cement plug at 1450-1550'; (4) 10 sacks of surface plug; and, (5) weld on plate and erect marker.

Subsurface Safety Valve: Manu. and Type _____ N/A Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Timothy Hartfield TITLE Opr. Engineer DATE February 24, 1982

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

APPROVED
(Orig. Sgd.) ROGER A. CHAPMAN
MAR 2 1982
FOR
JAMES A. GILLHAM
DISTRICT SUPERVISOR

TITLE _____ DATE _____

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

*See Instructions on Reverse Side