

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

1a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
B-2516

<p align="center">SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)</p>	
1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
CITIES SERVICE COMPANY	Tract 7
3. Address of Operator	9. Well No.
P. O. Box 1919 Midland, Texas 79702	9
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER <u>I</u> <u>2250</u> FEET FROM THE <u>South</u> LINE AND <u>1225</u> FEET FROM	Maljamar (G-SA)
THE <u>East</u> LINE, SECTION <u>29</u> TOWNSHIP <u>17S</u> RANGE <u>33E</u> NMPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4091' GR	Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 3950' Dolomite. Waiting on completion Unit with reverse equipment. Drilled a 7-7/8" hole to a T.D. of 3950' in Dolomite. Ran and set 98 jts. (3940') 5 1/2" OD 15.5# K55 csg @ 3950' and cemented with 800 sacks of Howco Lite w/1/4# Flocele and 10# salt/sack + 200 sacks of Class C w/1/4# Flocele & 2% CaCl2 cement. Plug down @ 0300 MDT on 9-20-81. Cement circulated to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Elmer Startz</u>	TITLE <u>Region Oper. Mgr.-Prod.</u>	DATE <u>9-23-81</u>
APPROVED BY <u>Jerry Sexton</u>	TITLE <u>Dist 1, Supr</u>	DATE <u>SEP 28 1981</u>
CONDITIONS OF APPROVAL, IF ANY:		