NO. OF COPIES RECEIVED		Form C-103
DISTRIBUTION		Supersedes Old C-102 and C-103
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
FILE		
U.S.G.S.		Sa. Indicate Type of Lease
LAND OFFICE		State Fee
OPERATOR		5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS  (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  USE "APPLICATION FOR PERMIT -" (EACH PROPOSALS.)		
1. OIL X GAS OTHER-		7, Unit Agreement Name SMGSAU
2. Name of Operator		8. Farm or Lease Name
Cities Service Company		Tract 4
3. Address of Operator		9. Well No.
P. O. Box 1919 - Midland, Texas 79702		13
4. Location of Well  1/85  North 2/00		10. Field and Pool, or Wildcat  Maljamar (G-SA)
UNIT LETTER	1485 FEET FROM THE NORTH LINE AND 2400 FEET FRO	" THE JAMES (O SK)
THE West LINE, SECT	TION 29 TOWNSHIP 17S RANGE 33E NMPR	
	15. Elevation (Show whether DF, RT, GR, etc.) 4092 GR	12. County Lea
Check Appropriate Box To Indicate Nature of Notice, Report or C		ther Data
		IT REPORT OF:
PERFORM REMEDIAL WORK  TEMPORARILY ABANDON  PULL OR ALTER CASING	PLUG AND ABANDON REMEDIAL WORK  COMMENCE DRILLING OPNS.  CHANGE PLANS CASING TEST AND CEMENT JQB X	ALTERING CASING PLUG AND ABANDONMENT
OTHER	OTHER Well Completio	n Data X
T.D. 4450' Dolomite & reverse equipment and 22 Jts. (771') 4" OD w/2% CaCl <sub>2</sub> cement. If the second of the second	Anhydrite, PBTD 4334'. Well complete. MIRU Complete deeper to A T.D. of 4450' in Dolomite 10.46# J55 FL4S Liner @ 3678-4449' and cemented PD @ 1515 MST on 12-18-81. Bumped plug w/1750# 30 min - OK. WOC 18 hrs. DO to 4449' and dum BTD of 4433'. Perf SA 2 SPF 4378-4388'. Total RIH w/4" RTTS on 2-3/8" EUE tbg. Set @ 4223'. run. 14 hr SITP 1275#. Reset RTTS @ 4223'. Pr/additives & 200# rock salt in 3 stgs. Max prese 100#. 10 min SIP 2400#. 84 hr SITP 1350#. Swbd Dmp 1 sk cmt on top. New PBTD 4334'. Perf Prese Total 30 holes (0.30" dia & 10.28" penetration) 0 & 28 BW/6 hrs. AZ w/4000 gal 15% HCl w/additives press incr on 1st blk, 300# incr on 2nd blk & 1 BO & 29 BW/3-1/2 hrs. Press csg to 1500#. Frace Sd, 39,000# 20-40 Sd & 200# rock salt & 100# BAD BAF w/100# incr. ISIP 2800#, 10 min SIP 2800#.	Completion Unit with & Anhydrite. Ran and set with 50 sx of Class C - Held OK. Press tested aped 1 sk cement plug @ 22 holes (0.30" dia & Swbd 30 BW/8 hrs. Gasses ess csg to 1500# - OK. AZ as 3700#, min press 3400#, trace oil & 53 BW/10 hrs. emier w/2 SPF @ 4230-36, Set RTTS @ 4006'. 14 h eves. Used 300#rock salt 3.2 BPM, ISIP 2900#, 10 min 00# incr on 3rd blk. 14 h ever Premier w/30,000 gal gell of in 3 equal stgs. Max of w/300# incr. 2nd blk
18. I hereby certify that the information	on above is true and complete to the best of my knowledge and belief.	

TITLE Region Opr. Mgr. Prod.

2-4-82

DATE\_

Swbd 9 BO & 115 BW/9 hrs. Ran and set 2-3/8" OD tubing @ 4321'. Ran rods and BHP. OCD POT tst pmpd 13 bbls of 36.5 gty oil & 109 BW/24 hrs. GOR TSTM.

SACE!AED

트리 [ 및 i의경본