, <i>•</i>		R. L. L. UBRINSHIN	isona approved.		
Form 3160-5 November 1983)	UN DISTATES OF	CX SUBAIT IN TRIP .TE.	Budget Bureau No. 1004-01 Expires August 31, 1985	35	
Formerly 9-331)	PEPARTMEN I OF THE INTERI	OR verse side)	5. LEASE DESIGNATION AND SERIAL NO	<u>.</u>	
	BUREAU OF LAND MANAGEMENT		LC-060549		
(Do not use this form Us	Y NOTICES AND REPORTS C n for proposais to drill or to deepen or plug b the "APPLICATION FOR PERMIT-" for succ pu		6. IF INDIAN, ALLOTTEE OR TRIDE NAN	đE	
I. OIL GAS GAS WELL	7. UNIT AUBREMENT NAME				
2. NAME OF OPERATOR	8. FARM OR LEASE NAME				
Amoco Production	Dunn Federal 🛿 ('and				
3. ADDRESS OF OPERATOR	9. WELL NO.				
P. O. Box 68, Ho	2				
4. LOCATION OF WELL (Report See also space 17 below.)	10. FIELD AND POOL, OR WILDCAT				
At surface	Und. Delaware				
1780' FNL (Unit F, S	11. SEC., T., S., M., OR BLK. AND SURVEY OR AREA				
, <i>,</i>	9-19-33				
14. PERMIT 20.	4. PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)				
	3691.3		12. COUNTY OR PARISH 13. STATE Lea NM		
16.	Check Appropriate Box To Indicate N	ature of Notice, Report, or C	Ither Data		
NOTIC	INT REPORT OF :				
TEST WATER SHUT-OFF	PCLL OR ALTER CASING	WATER SHUT-OFF	BEPAIRING WELL		
FRACTURS TREAT	MULTIPLE COMPLETE	FRACTURE TREATMENT	ALTTRING CASING		
SHOOT OR ACIDIZE	ABANDON*	SHOOTING OR ACIDIZING	ABANDONMENT [®] X		
REPAIR WELL	CHANGE PLANS	(Other)			
(Other)		(NOTE: Report results	of multiple completion on Well etion Report and Log form.)		
 DESCRIPE PROPOSED OR COM proposed work. If well nent to this work.) * 	PLETED OPERATIONS (Clearly state all pertinent is directionally drilled, give subsurface locati			n 5 tl-	
MISU, pulled rods RIH with CIBP and	s and pump and installed BOP d set at 7360', capped with	. POH with tubing, t 25 sx class C neat.	ubing anchor and tailpi Perfed 5100'-5101' w/4	pe	

SPF using a 3-3/8" casing gun. Ran cement retainer and set at 4890' and couldn't pump into perfs. Stung out of retainer and spotted 100' cement on top of retainer. Perfed 3030'-3031' w/4 SPF using a 3-1/8" gun and couldn't pump into perf. Perfed 550'-551' w/4 SPF using a 3-3/8" casing gun. Circulated 9-5/8" casing with 25 BW. Ran cement retainer and set at 310'. Circulated 9-5/8" casing with 110 sx class C neat cement. Stung out of retainer and pulled tubing. Spotted 60' cement at surface. Installed PXA marker and MOSU 6-28-84.

0+6-BLM, C 1-J. R. Barnett, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-GCC

SECURED Any C. Clark	TITLE	Assist.	Admin.	Analyst	DATE	7-12-84
APPROVED BY CONLITIONS OF APPROVAL, IF ANY:	TITLE				DATE	5 22.16

*See Instructions on Reverse Side

