TRI -	ovember 1983) Omerly 9-831) HOLES, HESBUREACOOS 22400 MANAGEMENT	Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND SERIAL NO. LC-060549
	SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for suca proposals.)	6. IF INDIAN, ALLOTTEE OR TRIDE NAME
	OIL GAS OTHER	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
	Amoco Production Company	Dunn Fodes B
	ADDRESS OF OPERATOR	9. WELL NO.
	P. O. Box 68, Hobbs, New Mexico 88240	2
4.	LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface	Und. Delaware 11. SEC., T., B., M., OR BLK. AND
	1780' FNL x 2180' FWL, Sec. 9	SURVEY OR AREA
	(Unit F, SE/4 NW/4)	9-19-33
14.	PERMIT NO. 15. ELEVATIONS (Show whether DF, RT, GR, etc.)	12. COUNTY OR PARISH 13. STATE
	3691.3' GL	Lea NM
16.	Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data	
	NOTICE OF INTENTION TO:	ANT REPORT OF:
	TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF FRACTURE TREAT SHOOT OF ACIDIZE REPAIR WILL CHANGE PLANS (Other) WATER SHUT-OFF FRACTURE TREATMENT SHOOTING OR ACIDIZING (NOTE: Report results Completion or Recognil	BEPAIRING WELL ALTERING CASING ABANDONMENT* of multiple completion on Well etion Report and Log form.)
	DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical nent to this work.)* Propose to plug and abandon as follows:	including estimated date of starting any l depths for all markers and zones perti-
	MISU and kill well with brine water. POH with rods, pump, and to set at 7360' and cap with 25 sxs Class 'C' neat cement. Perform RIH with cmt. retainer, set at 4900'. Establish an inj. rate into 100 sxs Class 'C' neat cement into perf. (This will place cmt. shoe). Spot a 250' (25 sxs Class 'C' neat cmt.) plug from 675' Spot a 50' surface plug (5 sxs Class 'C' neat), cap well, and en	ate 5100' with 4SPF. To perf and pump 100' above and below '-425' inside of csg.— *
*	Jaides of	
190 Sary Olar 6/14/84		
0+6-BLM, C 1-J. R. Barnett, HOU Rm. 21.156 1-F. J. Nash, HOU Rm. 4.206 1-GCC		
SIGNED Hay C. Care TITLE Assist. Admin. Analyst DATE 6/5/84		
2	APPROVED BY OIL Section TITLE F.E.	DATE 6/14/84

RECEIVED

UN 15 1984

!

H_{CS}SS OFFICE