

N. M. OIL CONS. COMMISSION  
P. O. BOX 1980  
HOBBS, NEW MEXICO 88240

Form Approved.  
Budget Bureau No. 42-R1424

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
Amoco Production Company

3. ADDRESS OF OPERATOR  
P. O. Box 68, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1780' FNL x 2180' FWL, Sec.9  
AT TOP PROD. INTERVAL: T-19-S, R-33-E  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA


REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) DST and Ran casing

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐  
☐



(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS  
U.S. GEOLOGICAL SURVEY  
ROSWEIL, NEW MEXICO

5. LEASE  
NM 060549

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Dunn Federal Com

9. WELL NO.  
2

10. FIELD OR WILDCAT NAME  
Und. Buffalo Penn Morrow

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
9-19-33

12. COUNTY OR PARISH  
Lea

13. STATE  
NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3691.3 GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled to TD of 9684'. Ran DST 12-18-81 results attached. Drilled to TD of 13703'. Ran 5-1/2 L-80 23#, N-80 17#, and N-80 20# casing set at 13703'. Cemented with 1850 sacks lite and 600 sacks class H with .3% Halad 4. Ran temperature survey top of cement 5890'. WOC 18 hours. Rig released 1-26-82. No further report until move in service unit.

0+6, USGS, R 1-Hou 1-W. Stafford, Hou 1-DMF 1-Susp

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Mark L. Luma TITLE Ast. Adm. Analyst DATE 2-1-82

ACCEPTED FOR RECORD  
ROGER A. CHAPMAN

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_ DATE \_\_\_\_\_

FEB 16 1982

U.S. GEOLOGICAL SURVEY  
POSWEIL, NEW MEXICO

\*See Instructions on Reverse Side