Form 9-331	UNI .D STATES	N. M. OIL CONS. COMMISE	Form approved.
(May 1963) DE	PARTMENT OF THE INTI	HOBBS, NEW MEXICO 88	5. LEASE DESIGNATION AND SERIAL NO.
	GEOLOGICAL SURVEY	,10000,11011111111111111111111111111111	NM 14790 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY (Do not use this form	NOTICES AND REPORT for proposals to drill or to deepen or p "APPLICATION FOR PERMIT—" for su	S ON WELLS lug back to a different reservoir. ch proposals.)	G. IF INDIAN, ADDOTAGE ON THESE SHARE
1. OIL GAS [V]			7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR	OTHER		8. FARM OR LEASE NAME
Grace Petroleum 3. ADDRESS OF OPERATOR	West Tonto "A" Fed. Com		
P.O. Drawer 2358 4. LOCATION OF WELL (Report See also space 17 below.) At surface	1-Y 10. FIELD AND POOL, OR WILDCAT Undesignated		
2450' FSL & 660' FWL of Sec. 25			11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
	15. ELEVATIONS (Show wheth	DD DD DD DD DD	Sec. 25, T-19-S, R-32-E
14. PERMIT NO.			Lea NM
Verbal on Skid We	Theck Appropriate Box To Indica		
	E OF INTENTION TO:		SSEQUENT REPORT OF:
TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (Other) 17. DESCRIBE PROPOSED OR COM	PULL OR ALTER CASING MULTIPLE COMPLETE ABANDON* CHANGE PLANS	(Note: Report re Completion or Rec	sing & test, perfs. sults of multiple completion on Well completion Report and Log form.)
proposed work. If well	is directionally drilled, give subsurface	iocations and measured and true	ettical depths for all markers and zones pert, 850' w/DV Tool @ 8937'.
F 1 D 1 9 1 1	15 jts 5 1/2" N-80 LTC,	1.65' 20# 4851.92' 2.20' LTC 6830.23' C 376.55' TC 622.52' TC 547.22' utt 401.36'	JUN 23 1982 OIL A. GAS BLS. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

4-12-82 Cmt'd 1st stage w/1550 sx Class 'H' cement w/.6% Halad 22A, .4% CFR-2, 5#/sx KCL, plug down 1:15 a.m. 4-12-82. Circulated thru DV Tool w/750 psi. Circulated 4 1/2

hrs.; Circulated out 50 sx o	cmt.		
111111	continue on next page.		
18. I hereby certify that the foregoing it true and correct			6 00 00
SIGNED \	TITLE District Production Manager	DATE	6-22-82
(This space for Federal CE FIED FOR RECORD			
APPROVED BY (ORIG SGD.) DAVID R. G	LASS	DATE	
CONDITIONS OF APPROVAL, IF ANY:	TITLE	DAIL	
0CT 1 8 1982			
001 10 1305			

ee Instructions on Reverse Side

Sundry Notice West Tonto "A" Fed. Comm. #1 Page 2

N. M. OIL CONS. COMMISSION P. O. BOX 1980 HOBBS. NEW MEXICO 88240

- 4-12-82 Cmt'd 2nd stage w/250 sx Class 'H' cement w/.6% Halad 22A, .4% CFR-2, 5#/ sx KCL, plug down 6:30 a.m., 4-12-82.
- 4-28-82 WOC 384 hrs. Drilled out DV Tool @ 8937'.
- 4-28-82 Tested BOP & 5 1/2" csg to 1500 psig.
- 5-3-82 Perf'd LWR Morrow intervals from 13,675' to 13,684' (10 holes) & 13,669' to 13,672' (4 holes).
- 5-4-82 Acidized perfs. 13,669' to 13,684' w/ 1000 gal Morrow Flo acid. Produced formation water.
- 5-8-82 Sqz'd perfs from 13,669' to 13,684' w/ 75 sx & reversed 20 sx, out.
- 5-10-82 Perf'd Morrow sand intervals w/ lJSPF, from 13,646' to 13,650' (5 holes), 13,531' to 13,535' (5 holes), & 13,454' to 13,460' (7 holes).
- 5-12-82 Acidize 1750 Morrowflo BC. Total 24 ball sealers, in 3 stages.

PEGETOVE 11

CHEA GUS U.S. GEOLOGICAL SURVEY ROSWELL, NEW MEXICO

BECHIARD

DCT 20 1940

Q. . . . **HOUS** Level ?