

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

T. Anhy	T. Canyon
T. Salt	T. Strawn
B. Salt	T. Atoka
T. Yates	T. Miss
T. 7 Rivers	T. Devonian
T. Queen 4410'	T. Silurian
T. Grayburg	T. Montoya
T. San Andres 5030'	T. Simpson
T. Glorieta	T. McKee
T. Paddock	T. Ellenburger
T. Blinebry	T. Gr. Wash
T. Tubb	T. Delaware Sand
T. Drinkard	T. Bone Springs 6736'
T. Abo	T.
T.	T.
Wolfcamp 9498'	T.
T. Penn	T.
T. Cisco (Bough C)	T.

Northwestern New Mexico

T. Ojo Alamo	T. Penn. "B"
T. Kirtland-Fruitland	T. Penn. "C"
T. Pictured Cliffs	T. Penn. "D"
T. Cliff House	T. Leadville
T. Menefec	T. Madison
T. Point Lookout	T. Elbert
T. Mancos	T. McCracken
T. Gallup	T. Ignacio Otzie
Base Greenhorn	T. Granite
T. Dakota	T.
T. Morrison	T.
T. Todilto	T.
T. Entrada	T.
T. Wingate	T.
T. Chinle	T.
T. Permian	T.
T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from... 4994' to 5002'

No. 3, from to

No. 2, from to

No. 4, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to feet

No. 2, from to feet

No. 3, from to feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
3660	4400		ANHY/DOL/SH				
4400	4900		ANHY/DOL/SD/SH				
4900	5520		DOL/SD/ANHY				
5520	6720		SD/DOL				
6720	6880		LS/DOL/SD/CHT				
6880	7200		DOL				
7200	8000		LS/SH/DOL				
8000	8815		DOL/SD				
8815	9280		DOL/SH/SD				
9280	9480		SD/DOL/SH				
9480	9715		DOL/SH/SD				
9715	9900		DOL/CHT/SH				