This form is to be filed with the appropriate i infort Office of the Division not later than 20 day — fter the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, liems 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Northwestern New Mexico

1.	Anny	T.	Canyon	_ T.	Ojo Alamo	T.	Penn. ''B''
т.	Salt	Т.	Strawn	<u> </u>	Kirtland-Fruitland		Penn. "C"
В.	Salt	T.	Atoka	.Т.	Pictured Cliffs	Т.	Penn. "D"
T.	Yates	 T .	Miss	. T.	Cliff House	Т.	Leadville
Τ.	7 Rivers	т	Devonian	T	lineofae	~	• • •
Т.	Queen4410	T.	Silurian	. Т.	Point Lookout	T.	Elbert
Т.	San Andres	_ т.	Simpson	. T.	Gallup	Т.	Ignacio Otzte
<u>,</u> Т.	Glorieta	Т.	McKee	- Ba	se Greenhorn	T.	Granite
T.	Paddock	<u> </u>	Ellenburger	. Т.	Dakota	T.	
т.	Blinebry	Т.	Gr. Wash	Т.	Morrison	Т.	
Т.	Tubb	_ т.	Granite	. T .	Todilto	Т.	
Т.	Drinkard	_ Т.	Delaware Sand	Т.	Entrada	т	· · · ·
Т.	Аьо	 T .	Bone Springs6736 '	. T.	Wingate		
T.	Wolfcamp 9490	_ Т.		Τ.	Chinle	Т.	
Τ.	Penn	<u> </u>		Τ.	Permian	T.	
Т	Cisco (Bough C)	_ T.		Τ.	Penn "A"	T.	
			OIL OR GAS	SF	NDS OR ZONES		
No.	1, from None		_to	No	. 4, from	*****	
							to
							to
					ATER SANDS		

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from None to	
No. 2, fromto	
No. 3, fromto	
No. 4, fromto	

FORMATION RECORD (Attach additional sheets if necessary)

From	То	Thickness in Feet	Formation	From	То	Thickness in Feet	Formation
3660	4400		ANHY/DOL/SH				
4400	4900		ANHY/DOL/SD/SH				
4900	5520		DOL/SD/ANHY				
5520	6720		SD/DOL				
6720	6880		LS/DOL/SD/CHT				
6880	7200		DOL				
7200	8000		LS/SH/DOL				
8000	8815		DOL/SD				
8815	9280		DOL/SH/SD				· · ·
9280	9480		SD/DOL/SH	-			
9480	9715		DOL/SH/SD				
9715	9900		DOL/CHT/SH				
							· · ·