

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-73

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG-1335	

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator MESA PETROLEUM CO.	8. Farm or Lease Name YESO STATE
3. Address of Operator P.O. BOX 2009 / AMARILLO, TX 79189	9. Well No. 1
4. Location of Well UNIT LETTER <u>F</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>13</u> TOWNSHIP <u>18S</u> RANGE <u>34E</u> NMPM.	10. Field and Pool, or Wildcat Wildcat Wolfcamp
15. Elevation (Show whether DF, RT, GR, etc.) 3980.4' GR	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded well with 17 1/2" hole on 2-1-83. Drilled to 400' and ran 12 jts 13 3/8", 48#, H40, ST&C casing set at 400'. Cemented with 420 sx "C" + 2% CaCl. PD at 1730, 2-2-83. Circulated 75 sx. Tested BOPs and casing to 1000 psi for 30 min--ok. Reduced hole to 12 1/4" and drilled ahead on 2-4-83. WOC total of 32 hours.

XC: NMOCD -H (O+2), CEN RCDS, ACCTG, MAT CONT, OPS (FILE), MIDLAND, HOBBS, PARTNERS

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED R.E. Mathis TITLE REGULATORY COORDINATOR DATE 2-4-83

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT 1 SUPERVISOR
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____ DATE FEB 10 1983

RECEIVED

FEB 9 1987

G.C. D. HOBBS OFFICE