

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG-604

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO CELEPH OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER: PxA	7. Unit Agreement Name
2. Name of Operator Amoco Production Company	8. Farm or Lease Name State DR
3. Address of Operator P. O. Box 68 Hobbs, NM 88240	9. Well No. 4
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>330</u> FEET FROM THE <u>East</u> LINE, SECTION <u>16</u> TOWNSHIP <u>19-S</u> RANGE <u>32-E</u> NMPM.	10. Field and Pool, or Wildcat Lusk, Northeast Yates
15. Elevation (Show whether DF, RT, GR, etc.) 3628.8' GL	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Pump tested for 10 days. Last 24 hours pumped 0 BO, 235 BW, and 0 MCFD. Moved in service unit 2-24-84. Pulled rods and pump. Nippled up blowout preventer and pulled tubing. Set a cast iron bridge plug at 2900' and capped with 250' plug of Class C neat cement. Spotted 150' cement plug 520' → 370'. Nippled down blowout preventer and cut off wellhead. Spotted 50' cement plug at surface. Welded on dry hole marker. Moved out service unit 2-27-84. Well plugged and abandoned 2-27-84.

0+5 - NMOC, H 1 - R. E. Ogden, Hou 1 - F. J. Nash, Hou 1 - CLF 1 - GDH, Bldg.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Cathy L. Ferman

TITLE Assistant Admin. Analyst

DATE 3-12-84

APPROVED BY [Signature]

OIL & GAS INSPECTOR

NOV 19 1984

CONDITIONS OF APPROVAL, IF ANY: