

MEASURED DEPTH FEET	DRIFT ANGLE D M	DRIFT DIRECTION D	COURSE LENGTH FEET	TRUE		VERTICAL SECTION FEET	R E C T A N G U L A R		DOGLEG SEVERITY DG/100FT
				VERTICAL DEPTH FEET	VERTICAL SECTION FEET		C O O R D I N A T E S	FEET	
0.	0 0	0	0.	0.00	0.00	0.00	0.00	0.00	0.00
100.	0 30	S 82 E	100.	100.00	0.17	0.06 S	0.43 E	0.50	0.50
200.	0 45	S 75 E	100.	199.99	0.66	0.28 S	1.50 E	0.26	0.26
300.	0 30	S 82 E	100.	299.99	1.14	0.50 S	2.57 E	0.26	0.26
400.	0 30	S 74 E	100.	399.98	1.54	0.68 S	3.42 E	0.07	0.07
500.	0 15	N 89 E	100.	499.98	1.79	0.76 S	4.07 E	0.27	0.27
600.	0 30	S 34 E	100.	599.98	2.21	1.05 S	4.63 E	0.42	0.42
700.	0 30	S 6 W	100.	699.97	3.06	1.88 S	4.83 E	0.34	0.34
800.	0 30	S 19 W	100.	799.97	3.84	2.73 S	4.64 E	0.11	0.11
900.	0 15	S 36 W	100.	899.97	4.32	3.31 S	4.34 E	0.27	0.27
1000.	0 30	S 4 W	100.	999.97	4.89	3.81 S	3.91 E	0.26	0.26
1100.	0 30	S 63 W	100.	1099.96	4.91	4.31 S	3.21 E	0.15	0.15
1200.	1 0	S 50 W	100.	1199.95	5.14	5.03 S	2.12 E	0.53	0.53
1300.	1 15	S 32 W	100.	1299.93	6.50	6.51 S	0.83 E	0.43	0.43
1387.	1 0	S 6 W	87.	1386.92	7.91	8.11 S	0.28 E	0.65	0.65
1570.	1 30	S 32 E	183.	1569.87	11.82	11.93 S	1.16 E	0.51	0.51
1632.	2 15	S 32 E	62.	1631.84	13.76	13.65 S	2.24 E	1.21	1.21
1625.	1 30	S 32 E	63.	1624.81	15.74	15.40 S	3.33 E	1.19	1.19
1757.	2 0	S 45 E	62.	1756.78	17.47	16.88 S	4.51 E	1.02	1.02
1819.	1 45	S 42 E	62.	1818.74	19.25	18.35 S	5.90 E	0.43	0.43
1882.	1 30	S 42 E	63.	1881.72	20.84	19.68 S	7.10 E	0.40	0.40
1944.	2 0	S 48 E	62.	1943.69	22.48	21.02 S	8.44 E	0.86	0.86
2006.	1 15	S 56 E	62.	2005.66	23.88	22.10 S	9.82 E	1.26	1.26
2069.	1 45	S 48 E	63.	2068.64	25.20	23.11 S	11.12 E	0.86	0.86
2131.	1 45	S 66 E	62.	2130.61	26.60	24.14 S	12.70 E	0.88	0.88
2193.	1 45	S 86 E	62.	2192.58	27.51	24.59 S	14.53 E	0.98	0.98
2256.	2 15	S 89 E	63.	2255.55	28.17	24.69 S	16.73 E	0.81	0.81
2318.	2 30	S 21 E	62.	2317.49	30.02	26.08 S	18.71 E	4.30	4.30
2380.	5 15	S 5 E	62.	2379.34	34.20	30.15 S	19.65 E	4.72	4.72
2443.	6 0	S 14 E	63.	2442.04	40.34	36.23 S	20.67 E	1.83	1.83