

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API# 30-025-28267

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- INJECTOR		7. Unit Agreement Name N. HOBBS (G/SA) UNIT
2. Name of Operator SHELL OIL COMPANY		8. Farm or Lease Name SECTION 33
3. Address of Operator P. O. BOX 991, HOUSTON, TEXAS 77001		9. Well No. 342
4. Location of Well UNIT LETTER 0, 125 FEET FROM THE SOUTH LINE AND 2730 FEET FROM THE WEST LINE, SECTION 33, TOWNSHIP 18-S, RANGE 38-E, NMPM.		10. Field and Pool, or Wildcat HOBBS (G/SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3631.6' GL, 3641.5' DF		12. County LEA

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-14-83: Ran 39 jts 1567' 24# K55 ST&C csg. Cemented w/400 sx HOWCO Lite + 2% CaCl2 + 1/4#/sx flocele plus 250 sx Class "C" + 2% CaCl2 + 1/4#/sx flocele, shoe @ 1565', bumped plug w/800 psi, float held OK, cement circulated.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. J. FORE TITLE SUPERVISOR REG. & PERMITTING DATE OCTOBER 21, 1983

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY SUPERVISOR TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
OCT 24 1983
O.C.D.
HOBBS OFFICE