N. M. OIL CONS. COMMISSION P. O. BOX 1980 HOBBS, NEW MEXICO 88240

Form Approved.

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM 12412
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil _M gas	Sloan Federal
well well other	9. WELL NO.
2. NAME OF OPERATOR	2
Sun Exploration & Production Co.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	East Lusk (Wolfcamp)
P. O. Box 1861, Midland, TX 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	Sec. 22, T-19-S, R-32-E
AT SURFACE: 990' FNI & 1980' FFI	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Unit letter B	Lea New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DE, DB, MD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	O'CLEVED OF
TEST WATER SHUT-OFF	A REPUITED &
FRACTURE TREAT	
REPAIR WELL	(NOTE: Report results multiple ton puttion or zone change on Form 9-310.)
PULL OR ALTER CASING	change on Form 9-310.
MULTIPLE COMPLETE	www.
ABANDON*	DIST. 6 N. M.
(other)	POSWELL, NEW ME
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	and partinent details, and give pertinent dates
including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertiner	lirectionally drilled, give subsurface locations and
measured and true vertical depths for all markers and zones pertiner	it to this work.)
Spud 9/17/83	
R & C 11 Jts 13-3/8 CS 450, Howco Cmt w/ 400 Sx	(s "C" w/ 2% Cacl, 1/4#
Flocele, FP 300-600, Plug OK Circ 100 Sxs	
0.125.103	
9/25/83 R & C 99 Jts 8-5/8 Csq. Cs 4107, FC 4063, DV 7	731 Unl Cmtd 1st Stage w/ 1665
Sxs Howco Lite w/ 18% Salt, & 1/4# Flocele, Tai	
FP 1500-2000, Circ 3 hrs thru DV tool, Circ 91	Sxs Cmt Cmtd 2nd stage W/
200 Sxs Howco Lite Tail w/ 200 Sxs "C" w/ 2% Ca	ocl FP 400-1300 Circ 175
Sxs cmt.	.0., 11 100 1000 0000
	64.6
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foreigning is true and correct	
SIGNED DEL TITLE Sr. Acct. Ass	St. DATE10/17/83
(This space for Federal or State office use)	
XI I NOVED D	DATE ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL, IF ANY:	(39C)