

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-101
Revised 10-1-78

API# 30-025-28413

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT --" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-	5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
2. Name of Operator SHELL OIL COMPANY	5. State Oil & Gas Lease No.
3. Address of Operator P. O. BOX 991, HOUSTON, TEXAS 77001	7. Unit Agreement Name N. HOBBS (G/SA) UNIT
4. Location of Well UNIT LETTER <u>N</u> <u>100</u> FEET FROM THE <u>SOUTH</u> LINE AND <u>1400</u> FEET FROM THE <u>WEST</u> LINE, SECTION <u>29</u> TOWNSHIP <u>18-S</u> RANGE <u>38-E</u> N.M.P.M.	8. Farm or Lease Name SECTION 29
	9. Well No. 242
	10. Field and Pool, or Wildcat HOBBS (G/SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3640.3' GL, 3650.3' DF	12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

12-17-83: Ran 39 jts 8-5/8" 24# K55 csg set @ 1511', cemented w/500 sx HOWCO Lite + 2% CaCl₂ and 1/4# flocele, followed w/250 sx Class "C" cmt + 2% CaCl₂, plugged down @ 1:30 PM, circ 196 sx cement to surface. Tested 8-5/8" csg w/1,000# OK.

NSL-1749

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>A. J. FORE</u>	TITLE <u>SUPERVISOR REG. & PERMITTING</u>	DATE <u>DECEMBER 21, 1983</u>
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT 1 SUPERVISOR		
APPROVED BY _____	TITLE _____	DATE <u>DEC 27 1983</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

DEC 27 1983

OCC
HOBBS CHIEF