

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name N. HOBBS (G/SA) UNIT
2. Name of Operator SHELL WESTERN E&P INC.		8. Farm or Lease Name SECTION 24
3. Address of Operator P. O. BOX 991, HOUSTON, TEXAS 77001		9. Well No. 413
4. Location of Well UNIT LETTER <u>A</u> , <u>1200</u> FEET FROM THE <u>NORTH</u> LINE AND <u>206</u> FEET FROM THE <u>EAST</u> LINE, SECTION <u>24</u> TOWNSHIP <u>18-S</u> RANGE <u>32E</u> NMPM.		10. Field and Pool, or Wildcat HOBBS (G/SA)
15. Elevation (Show whether DF, RT, GR, etc.) 3661.6' GL, 3671.6' DF		12. County LEA

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1-23-84: Ran 36 jts (1524') 8-5/8" 24# K55 ST&C csg. Cemented csg @ 1520' with 1500 sx HOWCO Lite cmt + 2% CaCl2 + 1/4#/sx flocele plus 250 sx Class "C" cmt + 2% CaCl2. Float collar @ 1474'. Bumped plug @ 5:15 AM w/900 psi, float held OK. Circulated 130 sx of cement.

NSL - 1749

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Jerry Sexton A. J. FORE TITLE SUPERVISOR REG. & PERMITTING DATE JANUARY 24, 1984

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE FEB 2 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JAN 26 1984

O.C.D.
HOBBES OFFICE