Form 9-331 Dec. 1973

HOBBS, NEW MEXIC. 38240 Form Approved.
Budget Bureau No. 42-R1424 HINITED STATES

ONITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-45225
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	
1. oil gas y other	8. FARM OR LEASE NAME Uncle Sam "25" Fed. Com.
2. NAME OF OPERATOR	9. WELL NO.
Nortex Gas & Oil Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR 79705	Undes. South Corbin Morrow Gas
One Petr. Center #6, Suite 201, Midland TX	11. SEC., T., R., M., OR BLK. AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA 25, T-18-S, R-32-E
AT SURFACE: 1980' FSL & 660' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE
AT TOTAL DEPTH:	Lea New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE	14. API NO.
REPORT, OR OTHER DATA	·
	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	KB 3781.3, GL 3754.4
TEST WATER SHUT-OFF	Dec Bu
SHOOT OR ACIDIZE	22 22 05v
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330)
MULTIPLE COMPLETE CHANGE ZONES	SS STATE
ABANDON*	그 모 그 모
(other) Subsequent report of commencement of dri	lling operations and setting
of surface casing. 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
measured and true vertical depths for an markers and zones pertin	ent to this work.)*
12-4-83 Spud 17½" hole @ 9:30 pm 12-3-83. MW 8	3.6, Vis 38.
12-5-83 RU & ran 12 joints of 13 3/8", 48#, H-4	10. ST&C csg. Set 0 492'
Kan I lexas Pattern shoe, 1-float colla	ar & 3 centralizers
Lemented w/550 sx Cl "C" + 2% CaCl + $\frac{1}{2}$	† Celloflake. Circulated
cement to surface. Plug down @ 1 pm 12	2-4-83. WOC. NU BOP.
12-6-83 Resume drilling operations. MW 9.5, Vis 31. 11" hole.	
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED	
(This space for Federal or State office use)	
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATEACCEPTED FOR RECORD

JAN 1 2 1984

RECKIVED

JAN 13 1984 Hobbs Office