

That the perforated interval from approximately 10,043 feet to 12,129 feet shall be effectively sealed by squeeze cementing prior to the initiation of injection operations into the well.

That the casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge at the surface or left open to the atmosphere to facilitate detection of leakage in the casing, tubing, or packer.

That the injection well or system shall be equipped with a pressure limiting device which will limit the wellhead pressure on the injection well to no more than 2435 psi.

That the Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the Devonian formation. That such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

That the operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the squeeze cementing operations, installation of disposal equipment, and of the mechanical integrity test so that the same may be inspected and witnessed.

That the operator shall immediately notify the supervisor of the Division's Hobbs district office of the failure of the tubing, casing, or packer, in said well or the leakage of water from or around said well and shall take such steps as may be timely and necessary to correct such failure or leakage.

PROVIDED FURTHER, That jurisdiction of this cause is hereby retained by the Division for such further order or orders as may seem necessary or convenient for the prevention of waste and/or protection of correlative rights; upon failure of applicant to comply with any requirement of this order after notice and hearing, the Division may terminate the authority hereby granted in the interest of conservation. That applicant shall submit monthly reports of the disposal operations in accordance with Rule 706 and 1120 of the Division Rules and Regulations.

That the Division Director may rescind or suspend this injection authority if it becomes apparent that the injected water is not being confined to the injection zone or it is endangering any fresh water aquifers.