

EXHIBIT I

North Hobbs (Grayburg/San Andres) Unit
Well No. 223
1770' FNL & 2405' FWL, Letter F, Section 30, T-18-S, R-38-E
Lea County, New Mexico

Produced Water

Maximum Injection Rate	9000 BWPD*
Average Injection Rate	N/A
Maximum Surface Injection Pressure	1100 PSI* (will not exceed 2400 psi bottom hole pressure)
Average Surface Injection Pressure	N/A

(* In accordance with Order No. R-6199-B, effective 10/22/01)

CO2 & Produced Gas

Maximum Injection Rate	15,000 MCFGPD*
Average Injection Rate	N/A
Maximum Surface Injection Pressure	CO2 – 1250 PSI* (will not exceed 2400 psi bottom hole pressure) CO2 w/produced gas – 1770 PSI* (will not exceed 2400 psi bottom hole pressure)
Average Surface Injection Pressure	N/A

(* In accordance with Order No. R-6199-B, effective 10/22/01)

Source Water - San Andres produced water

Injection Interval: Approximately 4000' to TD (4397')

Next higher oil zone - Byers (Queen) @ +/- 3680'

Next lower oil zone - Glorieta @ +/- 5300'

Occidental Permian Limited Partnership affirms that available geologic and engineering data has been examined resulting in the finding of no evidence of open faults or any other hydrologic connection between the disposal zone and any underground source of drinking water.