

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease
State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.
LG 1543

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator	8. Farm or Lease Name
Cities Service Oil & Gas Corp.	State DW
3. Address of Operator	9. Well No.
P.O. Box 1919 - Midland, Texas 79702	1
4. Location of Well	10. Field and Pool, or Wildcat
UNIT LETTER J, 1980 FEET FROM THE South LINE AND 1650 FEET FROM THE East LINE, SECTION 12 TOWNSHIP 18S RANGE 33E NMPM.	Wildcat (Wolfcamp)
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4096.6 GR	Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 5283' Dolomite. Prep to drill ahead. Drilled 11" hole from 500' to a T.D. of 5283' in Dolomite. Ran & set 31 jts. (1287.52') of 8-5/8" OD 24# & 93 jts. (3968.14') of 8-5/8" OD 32# casing at 5283' and cemented with 3805 sacks of TLW with 15# salt, 0.25# flocele & 5.0# silsonite/sack + 300 sacks of Class C cement. Cement circulated. PD at 0730 MST on 3-2-84. WOC 72 hrs. Tested 8-5/8" casing to 2000# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Startz TITLE Region Opr. Mgr. - Prod. DATE 3-6-84

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE MAR 13 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
MAR 12 1984  
O.C.D.  
HOBBY OFFICE