

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
V-803	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		7. Unit Agreement Name
2. Name of Operator Morris R. Antweil		8. Farm or Lease Name State H.S.
3. Address of Operator P. O. Box 2010		9. Well No. 1
4. Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>36</u> TOWNSHIP <u>18S</u> RANGE <u>38E</u> NMPM.		10. Field and Pool, or Wildcat Undesignated
15. Elevation (Show whether DF, RT, GR, etc.) 3599.3 GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input checked="" type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

San Andres perforations 4480'-4497' pumped 50 BWPD with trace of oil. Squeezed with 100 sx class "C" cement containing 6/10% CFR-2 and 3#/sk salt and 75 sx class "C" cement containing 3#/sk salt and 3#/sk sand. Squeezed with 65 sx in perfs. to 5000 psi. Drilled out and tested to 2000 psi. Drilled CIBP at 4750'. Set CIBP at 6220' and capped with 20' cement. Perforated Glorieta with single shots at 5983 1/2, 5985, 5986, 5987, 5988 and 5989 (6 holes). Acidized with 2000 gals 15% NE-FE acid at 4.3 BPM and 4600 psi. ISIP 2400 15 Min. SIP 550. Swabbed 113 BW in 4 hours. Ran rods and pump.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Agent DATE Oct. 3, 1984

ORIGINAL SIGNED BY UNIT SECTION  
DISTRICT 1-1000-1000

APPROVED BY [Signature] TITLE  DATE OCT - 4 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

OCT - 4 1984

U.S. DEPT. OF JUSTICE  
HONORABLE ATTORNEY GENERAL