

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1543	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 2
4. Location of Well UNIT LETTER <u>K</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>1880</u> FEET FROM THE <u>West</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18S</u> RANGE <u>33E</u> N.M.P.M.		10. Field and Pool, or Wildcat Undesig. (Bone Springs)
15. Elevation (Show whether DF, RT, GR, etc.) 4043' GR		12. County Lea

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 9050' Chert, Lime & Sand. Waiting on completion unit. Drilled a 7-7/8" hole from 3300' to a T.D. of 9050' in Chert, Lime & Sand. Ran and set 166 Jts.(6674.33') 5-1/2" OD 15.5# and 56 Jts.(2363.76') 5-1/2" OD 17# casing @ 9050' and cemented with 2000 sacks of Class H-Pozmix A 50/50 w/3# salt and 0.3 of 1% Halad 22-A/sack cement. PD @ 2105 MDT on 5-30-84. Displace plug w/FW. Bumped float w/2600# - OK. Set slips. CO casing. ND BOP's. NU wellhead. Ran Temp. Survey. Top of cement @ 2870'.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Elmer Startz</u>	TITLE <u>Reg. Opr. Mgr. - Prod.</u>	DATE <u>6-1-84</u>
ORIGINAL SIGNED BY JERRY SEXTON DISTRICT I SUPERVISOR		
APPROVED BY _____	TITLE _____	DATE <u>JUN 4 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		

f

RECEIVED

JUN 4 1984

O.C.D.  
HOBBS OFFICE