

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1543	

## SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER- Drilling		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 3
4. Location of Well UNIT LETTER <u>H</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat Undesig. (Bone Springs)
15. Elevation (Show whether DF, RT, GR, etc.) 4098' GR		12. County Lea

## Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

## SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 350' Red Beds. Prep to drill ahead. MIRU a rotary and spudded a 17-1/2" hole @ 1630 MDT on 6-1-84 and drilled to a T.D. of 350' in Red Beds. Ran and set 10 Jts. (335') 13-3/8" OD 48# casing @ 350' and cemented w/300 sacks of TLW w/0.25# flocele and 2% CaCl<sub>2</sub>/sack + 200 sacks of Class C w/2% CaCl<sub>2</sub>/sack cement. PD @ 0200 MDT on 6-2-84. Circulated 130 sacks of cement to surface. WOC 9 hrs. Tested 13-3/8" OD casing to 500# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Eddie W. Seay TITLE Reg. Opr. Mgr. - Prod. DATE 6-5-84

Eddie W. Seay

APPROVED BY Oil & Gas Inspector TITLE  DATE JUN 7 1984

CONDITIONS OF APPROVAL, IF ANY: