Application for 0. or Gas Waste Disposal Well Permuc

Page 2

VI. Wells With Area of Review (Continued) Cities Service Oil and Gas Corporation, State DW #10 990' FSL, 2130' FWL, Section 12, Township 18S, Range 33E Bone Springs oil well (8708-8761') PBTD 9047', MID 9097' NMOCD potential(12-17-84): Flowed 254 bbls 39.6° API gty oil and 2 bbls water in 20 hours on 1" choke, FTP 40#, GR 466 MCFD, GOR 1528, CDA 230 BOPD Construction: 13.375" 48# H40 set at 350' 8.625" 24# and 32# K55 set at 3150' 5.5" 15.5# and 17# K55 and N80 set at 9097' Cities Service Oil and Gas Corporation, State DW #11 990' FSL, 660' FWL, Section 12, Township 18S, Range 33E Bone Springs oil well (8695-8741') PBTD 9008', MTD 9050' NMOCD potential (5-6-85): Pumped 51 bbls of 38.7° API gty oil and 7 bbls of water in 24 hours, GR 58 MCFD, GOR 1137, 6 X 144" SPM, CDA 51 BOPD Construction: 13.375" casing set at 375' 8.625" casing set at 3160' 5.5" casing set at 9050' Cities Service Oil and Gas Corporation, Federal AB #1 1980' FNL, 660' FEL, Section 11, Township 18S, Range 33E Bone Springs oil well (8631-8685') PBTD 9757', MITD 13,780' NMOCD potential (5-2-85): Pumped 373 bbls of 38.1° API gty oil and 20 bbls load water in 16 hours, GR 262 MCFD, GOR 468, CDA 230 BOPD Construction: 13.375" 48# H40 set at 356' 9.625" 36# and 40# K55 and N80 set at 5300' 5.5" 17# N80 and S95 set at 13,779' Miller, British American State #2 660' FNL, 1980' FEL, Section 12, Township 18S, Range 33E Drilled and abandoned San Andres test (7-18-56) MTD 5481' Construction: 8.625" casing set at 213'

Plugging information unavailable

-

- --

