MO. OF COPIES RECEIVED	•
DISTRIBUTION	Form C-103
SANTAGE	Supersedes Old
FILE NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
U.S.G.S.	
LAND OFFICE	Sa, indicate Type of Lease
OPERATOR	State X Fee
	5. State Ci. 6 Gas Lease No.
CHIDDA NOTICES	LG 1543
SUNDRY NOTICES AND REPORTS ON WELLS USE "APPLICATION FOR PERMIT -" IFORM C-101) FOR SUCH PROPOSALS.) []	
WELL X CAS WELL OTHER-	7. Unit Agreement Name
Cities Service Oil and Cae Communic	8. Farm of Lease Name
Cities Service Oil and Gas Corporation	State DW
	9. Well No.
P.O. Box 1919 - Midland, Texas 79702	4
	10. Field and Pool, or Wildcat (Bon
UNIT LETTER F 1880 FEET FROM THE NORTH LINE AND 1980 FEET FROM	Mescalero Escarpe Spr
	THE THE PARTY OF T
THE West LINE, SECTION 12 TOWNSHIP 185 RANGE 33E NAPPM.	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
4105' GR	Lea ()
Check Appropriate Box To Indicate Nature of Notice, Report or Oth	or Data
NOTICE OF INTENTION TO: SUBSEQUENT	DEBORT OF
	REPORT OF:
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK	
TEMPORARILY ABANDON COMMENCE DRILLING OPNS.	ALTERING CASING
PULL OR ALTER CASING CHANGE PLANS CASING TEST AND CEMENT JOB X	PLUG AND ABANDONMENT
OTHER	_
ОТИСЯ	
17 Describe Eropoped of Communication	
17. Describe Proposed of Completed Operations (Clearly state all pertinent details, and give pertinent dates, including e work) SEE RULE 1103.	stimuted date of starting any propused
	, and any proposed
T.D. 9050' Dolomite & Chert. Waiting on completion unit. Drilled a 7-	7.00
to a T.D. of 9050' in Dolomita & Chart Pan and and 157 14 (cons and	//8" hole from 3300'
to a T.D. of 9050' in Dolomite & Chert. Ran and set 157 Jts. (6623.07') 56 Jts. (2414.93') 5-1/2" OD 17# casing @ 9050' and cemented w/1925 sack Poz A w/3# salt & 0.3% Halad 22A cement Plug down @ 1700 MDT and 7.00	5-1/2" OD 15.5# and
Poz A w/3# salt & 0.3% Halad 22A cement. Plug down @ 1700 MDT on 7-22- w/2000# - OK. WOC 4 hrs. Ran Town Sunvey. Tax of a reserved a career	34. Bumped float
	D DODL
CO casing and NIL wollhoad	D BUP's, set slips,
w/2000# - OK. WOC 4 hrs. Ran Temp. Survey. Top of cement @ 2700'. N	D BUP's, set slips,
CO casing and NU wellhead.	b Bup's, set slips,
	D BUP'S, SET STIPS,
	D BUP'S, SET STIPS,
CO casing and NU wellhead.	D BUP"S, SET STIPS,
	D BUP"S, SET STIPS,
	D BUP'S, SET STIPS,
	D BUP'S, SET STIPS,
	D BUP'S, SET STIPS,
and no herricul.	D BUP'S, SET STIPS,
and no herricul.	D BUP'S, SET STIPS,

18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Start TITLE Reg. Opr. Mgr. - Prod.

ORIGINAL VIEW TITLE Reg. Opr. Mgr. - Prod.

DATE 7-24-84

APPROVED BY TITLE OATE

CONDITIONS OF APPROVAL, IF ANY: