

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fed <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1543	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 5
4. Location of Well UNIT LETTER <u>P</u> <u>660</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18S</u> RANGE <u>33E</u> N.M.P.M.		10. Field and Pool, or Wildcat (Bone) Mescalero Escarpe Springs
15. Elevation (Show whether DF, RT, GR, etc.) 4089' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 9030' Lime & Chert. Waiting on completion unit. Drilled a 7-7/8" hole from 3300' to a T.D. of 9030' in Lime and Chert. Ran and set 159 Jts.(6677.37') 5-1/2" OD 15.5# and 53 Jts. (2383.57') 5-1/2" OD 17# casing @ 9030' and cemented w/1020 sacks of Halco lite w/0.25# flocele & 0.5% Halad 9/sack + 315 sacks of Class H 50/50 Pozmix A w/3# salt & 0.3% Halad 22/sack cement. PD @ 1600 CDT on 8-15-84. Bumped float w/1500# - OK. WOC 4 hrs. Ran temp. survey. TOC @ 3300'. PU BOP's, set slips, CO casing and ND BOP's.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Stautz TITLE Reg. Opr. Mgr. - Prod. DATE 8-16-84

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT SUPERVISOR DATE 8-16-1984

CONDITIONS OF APPROVAL, IF ANY

RECEIVED

AUG 17 1984

O.C.D.
NOBES OFFICE